



(1) EC-TYPE-EXAMINATION CERTIFICATE (Translation)

(2) Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres - **Directive 94/9/EC**



(3) EC-type-examination Certificate Number:

PTB 99 ATEX 1164

(4) Equipment: Load, master, motor and safety switch of type GHG 26. R

(5) Manufacturer: CEAG Sicherheitstechnik GmbH

(6) Address: Neuer Weg Nord 49, 69412 Eberbach

(7) This equipment and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

(8) The Physikalisch-Technische Bundesanstalt, notified body No. 0102 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres, given in Annex II to the Directive.

The examination and test results are recorded in the confidential report PTB Ex 00-19265.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 50014:1997

EN 50018:1994

EN 50019:1994

(10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.

(11) This EC-type-examination Certificate relates only to the design and construction of the specified equipment in accordance with Directive 94/9/EC. Further requirements of this Directive apply to the manufacture and supply of this equipment.

(12) The marking of the equipment shall include the following:

II 2 G EEx de IIC T6

Zertifizierungsstelle Explosionsschutz

Braunschweig, October 02, 2000

By order:

Dr.-Ing. U. Klausmeyer
Regierungsdirektor



(13)

SCHEDULE

(14)

EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 1164

(15)

Description of equipment

The load, master, motor and safety switch of type GHG 26.R... is composed of one or two enclosures made of plastics, sheet steel or Cu-Ni alloy of the type of protection increased safety "e" with incorporated - separately certified - built-in switch components and, if and when required, one or two auxiliary switches of the type of protection flameproof enclosure "d" and, depending on the enclosure size, with incorporated - separately certified - measuring instruments, pushbuttons, indicating lamps and terminals. Via an additional operating knob, a leading converter can be controlled in front of the cut-off point proper.

Cable entries, for which a separate certificate has been issued, are used for external connection.

Technical data

Built-in switch component GHG 26.R.... (PTB 99 ATEX 1062 U)

Utilization category AC 1

Rated voltage U_e	up to	690 V
Rated current I_e	max.	180 A

Utilization category AC 3

Rated voltage U_e	up to	400 V	500 V	690 V
Rated current I_e	max.	180 A	150 A	125 A

Rated cross-section with appertaining terminal end

50 mm ² for 125 A
70 mm ² for 150 A
120 mm ² for 185 A

Built-in switch component GHG 2.. ... R.... (PTB 98 ATEX 1117 U)

Utilization category AC 1

Rated voltage U_e	up to	690 V
Rated current I_e	max.	20 A

Utilization category AC 3

Rated voltage U_e	up to	400 V	500 V	690 V
Rated current I_e	max.	20 A	16 A	10 A

Utilization category AC 11

Rated voltage U_e	up to	230 V	400 V	590 V
Rated current I_e	max.	8 A	6 A	6 A

Physikalisch-Technische Bundesanstalt



Braunschweig und Berlin

SCHEDULE TO EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 1164

Utilization category DC 11

Rated voltage U_e	up to	24 V	110 V	230 V
Rated current I_e	max.	6 A	0,6 A	0,4 A
L/R		60 ms	30 ms	20 ms

Rated cross-section max. 2,5 mm² (finely stranded) or 4 mm² (single core)

Ambient temperature range: -55 °C to +45 °C

In accordance with the relevant provisions, rated values other than those stated above are permissible if the making and breaking capacity is complied with; they must be specified by the manufacturer, dependent on the mode of operation, utilization category, etc.

The composition of the symbol specifying the type of protection depends on the types of protection of the components used.

(16) Test report PTB Ex 00-19265

(17) Special conditions for safe use

none

(18) Essential health and safety requirements

The tests carried out and their positive results show that the load, master, motor and safety switch of type GHG 26.R...meets the requirements of Directive 94/9/EC and of the standards stated on the cover sheet.

Zertifizierungsstelle Explosionsschutz

Braunschweig, October 02, 2000

By order:

Dr.-Ing. U. Klausmeyer
Regierungsdirektor



sheet 3/3

EC-type-examination Certificates without signature and official stamp shall not be valid. The certificates may be circulated only without alteration. Extracts or alterations are subject to approval by the Physikalisch-Technische Bundesanstalt. In case of dispute, the German text shall prevail.

1st SUPPLEMENT

according to Directive 94/9/EC Annex III.6

to EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 1164

(Translation)

Equipment: Load interrupter, master, motor protection and safety switch type GHG 26. R

Marking:  II 2 G EEx de IIC T6

Manufacturer: CEAG Sicherheitstechnik GmbH

Address: Neuer Weg Nord 49
69412 Eberbach, Germany

Description of supplements and modifications

The load interrupter, master, motor protection and safety switch type GHG 26. R may now also be used in areas where potentially explosive atmospheres with dust/air mixtures may occasionally occur.

Therefore the marking is changed into:


 II 2 G/D EEx de IIC T6 IP66 T 53 °C

Test report: PTB Ex 01-11121

Zertifizierungsstelle Explosionsschutz

By order:

Braunschweig, May 7, 2001


Dr.-Ing. U. Klausmeyer
Regierungsdirektor

