



1. EC-TYPE EXAMINATION CERTIFICATE

- 2. Equipment or Protective System Intended for use in Potentially Explosive Atmospheres Directive 94/9/EC
- 3. EC-Type Examination Certificate Number: ITS09ATEX16438X
- 4. Equipment or Protective System: FlexLevel Switch 4401 2xx
- 5. Manufacturer: Baumer A/S
- 6. Address: Jacob Knudsens Vej 14, DK-8230 Aabyhoj, Denmark
- This equipment or protective system and any acceptable variation thereto is specified in the schedule to this
 certificate and the documents therein referred to.
- 8. Intertek Testing and Certification Limited, notified body number 0359 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Intertek Report Ref ETS 3592 dated 10 September 2009

- Compliance with the Essential Health and Safety Requirements has been assured by compliance with standards EN 61241-0: 2006, EN 61241-1: 2004 except in respect of those requirements referred to at item 18 of the Schedule.
- 10. If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.
- 11. This EC-Type examination certificate relates only to the design and construction of the specified equipment or protective system in accordance to the directive 94/9/EC. Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.
- 12. The marking of the equipment or protective system shall include the following:-

⟨Ex⟩ II 1D Ex tD A20 IP67 100°C

Peter T. Lauritzen

Deputy Certification Officer

Date: 30-09-2009

Intertek Testing & Certification Limited Intertek House, Cleeve Road, Leatherhead, Surrey, KT22 7SB Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977

http://www.intertek.com

Registered No 3272281 Registered Office: 25 Savile Row London W1X 1AA

This certificate may only be reproduced in its entirety and without any change, schedule included and is subject to Intertek Testing and Certification Conditions for Granting Certification.

Sheet 1 of 4





- 13. SCHEDULE
- 14 EC-TYPE EXAMINATION CERTIFICATE NUMBER ITS09ATEX16438X
- Description of Equipment or Protective System

FlexLevel Switch 4401xxx is used for level measuring of liquids or powder. The functionality is based on the DK value of the media. The product contains a printed circuit board which contains all the electronic for the functionality. This circuit board is mounted in a plastic housing and encapsulated in Silicone gel. Terminals are placed on the outside of this plastic housing. This plastic housing is again mounted in a stainless steel AISI 316L housing (diameter 55mm). The cable connections is lead through a cable gland made of brass or plastic or through a M12 plug mounted in the stainless steel housing. The sensor is terminated internally to the screw terminals on the plastic housing.

| FlexLevel Switch | 4401 | x | x | x |
|---|------|---|---|---|
| Safety: | | | | |
| Standard | | 0 | | |
| 1G (Zone 0,1,2) | | 1 | | |
| 1D (Zone 20, 21, 22) | | 2 | | |
| 3G (Zone 2) | | 3 | | |
| Electrical connections: | | | | |
| Plug, M12 | | | 1 | |
| Cable gland Brass M16 | | | 2 | |
| Cable gland Polyamide M16 | | | 3 | |
| Process connection: | | | | |
| G1/2, PEEK tip | | | | 1 |
| 3A Hygienic connection DN38 | | | | 2 |
| G1/2, PEEK tip, sliding connection, 100mm | | | | 3 |
| G1/2, PEEK tip, sliding connection, 250mm | | | | 4 |

Input specifications.

Ui: 30Vdc Ii: 100mA

16. Report Number:

Intertek Report ETS3592 dated 10 September, 2009

Intertek Testing & Certification Limited
Intertek House, Cleeve Road, Leatherhead, Surrey, KT22 7SB
Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977

http://www.intertek.com
Registered No 3272281 Registered Office: 25 Savile Row London W1X 1AA

This Certificate is the property of Intertek Testing and Certification Ltd and is subject to Intertek Testing and Certification Conditions for Granting Certification.

Sheet 2 of 4





- 13. SCHEDULE
- 14 EC-TYPE EXAMINATION CERTIFICATE NUMBER ITS09ATEX16438X
- 17. CONDITIONS OF CERTIFICATION:
 - (a). Special Conditions for safe use

It is essential that the media temperature is considered according to the below tables and the description in the Installation Manual provide by the manufacturer.

FlexLevel 4401 2x1/2 (G1/2, PEEK tip and 3A Hygienic connection DN38)

| Ambient temperature | Maximum media/process temperature | T-Class |
|---------------------|-----------------------------------|---------|
| -40°C < Tamb < 85°C | 85°C | 100 °C |
| -40°C < Tamb < 60°C | 95°C (*) | 100 °C |
| -40°C < Tamb < 40°C | 115°C (*) | 100 °C |

(*) provided that the sensor tip at the sliding connection is the only part in contact with the media

FlexLevel 4401 2x3 (G1/2, PEEK tip, sliding connection, cooling neck, 100mm)

| Ambient temperature | Maximum media temperature | T-Class |
|---------------------|---------------------------|---------|
| -40°C < Tamb < 85°C | 85°C | 100 ℃ |
| -40°C < Tamb < 60°C | 150°C (*) | 100 °C |
| -40°C < Tamb < 40°C | 175°C (*) | 100 °C |

^(*) provided that the sensor tip at the sliding connection is the only part in contact with the media

FlexLevel 4401 2x4 (G1/2, PEEK tip, sliding connection, cooling neck, 250mm)

| I TONEOTO THOU ENT (OTIZ) I LE | it up, sharing confliction, cooming neon, ze | Ortinity | |
|--------------------------------|--|----------|--|
| Ambient temperature | Maximum media temperature | T-Class | |
| -40°C < Tamb < 85°C | 85°C | 100 °C | |
| -40°C < Tamb < 60°C | 195°C (*) | 100 °C | |
| -40°C < Tamb < 40°C | 200°C (*)(**) | 100 °C | |

(*) provided that the sensor tip at the sliding connection is the only part in contact with the media

(**) Maximum allowed media/process temperature.

The following warning must be present on the marking plate:
"DO NOT OPEN WHEN AN EXPLOSIVE DUST ATMOSPHERE IS PRESENT"

- (b). Conditions For Use (Routine Tests)
- 18. Essential Health and Safety Requirements (EHSR's)

The relevant EHSR's have been identified and assessed in Intertek Report ETS 3592 dated 10 September 2009.

Intertek Testing & Certification Limited
Intertek House, Cleeve Road, Leatherhead, Surrey, KT22 7SB
Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977

http://www.intertek.com

Registered No 3272281 Registered Office: 25 Savile Row London W1X 1AA

This Certificate is the property of Intertek Testing and Certification Ltd and is subject to Intertek Testing and Certification Conditions for Granting Certification.

Sheet 3 of 4





- 13. SCHEDULE
- 14 EC-TYPE EXAMINATION CERTIFICATE NUMBER ITS09ATEX16438X
- 19. Drawings and Documents

| Document No. | Sheets | Document Title | Issue | Date (yyyy/mm/dd) |
|-----------------|--------|---|-------|----------------------|
| 5520-533 | 1 | FlexLevel Switch 4xxx | C1 | 2009-11-02 |
| 5551-533 | 1 | Assembly | D2 | 2009-08-25 |
| 5502-007 | 1 | FlexLevel Switch Samlingstegning | B2 | 2009-06-15 |
| 5502-005 | 1 of 3 | Instrument Drawings ½" Nippel | A2 | 2009-07-06 |
| 5502-005 | 2 of 3 | DN38 3A Hygeenic | A2 | 2009-06-17 |
| 5502-005 | 3 of 3 | Sliding connection with welding parts and seal / clamp ring | A2 | 2009-07-07 |
| 5502-008 | 1 | Samling Control Unit | A2 | 2009-04-14 |
| 3031_0A0 | 1 1 | Ujaca A55 mm Mad live indikatara. | , R1, | 2009-11-22 |
| 3031-050 | 1 | Dæksel for låg med lys. LSM | B1 | 2009-10-12 |
| 3011087 | 1 | Housing Ø55 | A1 | 2009-04-21 |
| 2008970 | 1 | Etiket FlexLevel Switch 4401 2xx Ex Dust | A1 | 2009-08-25 |

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Testing & Certification Limited
Intertek House, Cleeve Road, Leatherhead, Surrey, KT22 7SB
Tel: + 44 (0)1372 370900 Fax: +44 (0)1372 370977

http://www.intertek.com

Registered No 3272281 Registered Office: 25 Savile Row London W1X 1AA

This Certificate is the property of Intertek Testing and Certification Ltd and is subject to Intertek Testing and Certification Conditions for Granting Certification.

Sheet 4 of 4





SUPPLEMENTARY EC-TYPE EXAMINATION CERTIFICATE

- 2. Equipment or Protective System Intended for use in
 - 3. Supplementary EC-Type Examination Certificate Number: ITS09ATEX16438X
 - 4. Equipment or Protective System: FlexLevel Switch 4401 2xx
 - Manufacturer: Baumer A/S
 - 6. Address: Jacob Knudsens Vej 14, DK-8230 Aabyhoj, Denmark
 - 7. This supplementary certificate extends EC-Type Examination Certificate Number to apply to equipment or protective systems designed and constructed in accordance with the specification set out in the Schedule of the said Certificate but having variations specified in the Schedule attached to this certificate and the documents therein referred to

Intertek Report Ref 09 041750 ETS 3592

This Supplementary Certificate shall be held with the original Certificate

P Moss Certification Officer 30th July 2010

Intertek Testing & Certification Limited
Deeside Lane, Chester, CH1 6DD.
Tel: + 44 (0)1244 882590 Fax: +44 (0)1244 882599

Pagistavad No 2272201 Degistered Offices 25 Cavilla David and as N

This certificate may only be reproduced in its entirety and without any change, schedule included and is subject to Intertek Testing and Certification Conditions for Granting Certification.

Sheet 1 of 3





Schedule

SUPPLEMENTARY EC-TYPE EXAMINATION CERTIFICATE NUMBER: ITS09ATEX16438X-V1

VARIATION ONE

Description of the Variation to the Equipment or Protective System.

To permit the following change:

FlexLevel Switch 4401 2xx will know be known as the Level Switch LFFS 2xx and is identical in every other aspect.

| Level Switch | LFFS | X | X | X |
|---|------|---|---|---|
| Safety: | | | | |
| Standard | | 0 | | |
| 1G (Zone 0,1,2) | | 1 | | |
| 1D (Zone 20, 21, 22) | | 2 | | |
| 3G (Zone 2) | | 3 | | |
| Electrical connections: | | | | |
| Plug, M12 | | | 1 | |
| Cable gland Brass M16 | | | 2 | |
| Cable gland Polyamide M16 | | | 3 | |
| Process connection: | | | | |
| G1/2, PEEK tip | | | | 1 |
| 3A Hygienic connection DN38 | | | | 2 |
| G1/2, PEEK tip, sliding connection, 100mm | | | | 3 |
| G1/2, PEEK tip, sliding connection, 250mm | | | | 4 |

Report No.

Intertek Report Ref: See original Report

CONDITIONS OF CERTIFICATION

(a) Special Conditions for Safe Use:

Level Switch LFFS 2x1/2 (G1/2, PEEK tip and 3A Hygienic connection DN38)

| Level Switch Liff 3 2x 112 (G 112, F LLK tip and 3x fryglefile Conflection DN30) | | | | | |
|--|-----------------------------------|---------|--|--|--|
| Ambient temperature | Maximum media/process temperature | T-Class | | | |
| -40°C < Tamb < 85°C | 85°C | 100 °C | | | |
| -40°C < Tamb < 60°C | 95°C (*) | 100 °C | | | |
| -40°C < Tamb < 40°C | 115°C (*) | 100 °C | | | |

^(*) provided that the sensor tip at the sliding connection is the only part in contact with the media

Level Switch LFFS 2x3 (G1/2, PEEK tip, sliding connection, cooling neck, 100mm)

| т ′ | Ambient temperature | iviaximum media temperature | ı-Class |
|-----|---------------------|-----------------------------|---------|
| | -40°C < Tamb < 85°C | 85°C | 100 °C |
| | -40°C < Tamb < 60°C | 150°C (*) | 100 °C |
| | -40°C < Tamb < 40°C | 175°C (*) | 100 °C |

^(*) provided that the sensor tip at the sliding connection is the only part in contact with the media

Intertek Testing & Certification Limited
Deeside Lane, Chester, CH1 6DD
Tel: + 44 (0)1244 882590 Fax: +44 (0)1244 882599

http://www.intertek.com Registered No 3272281 Registered Office: 25 Savile Row London W1X 1AA

This Certificate is the property of Intertek Testing and Certification Ltd and is subject to Intertek Testing and Certification Conditions for Granting Certification.

Sheet 2 of 3





Schedule

SUPPLEMENTARY EC-TYPE EXAMINATION CERTIFICATE NUMBER: ITS09ATEX16438X-V1

Level Switch LFFS 2x4 (G1/2, PEEK tip, sliding connection, cooling neck, 250mm)

| | the state of the s | | | |
|---------------------|--|---------|--|--|
| Ambient temperature | Maximum media temperature | T-Class | | |
| -40°C < Tamb < 85°C | 85°C | 100 °C | | |
| -40°C < Tamb < 60°C | 195°C (*) | 100 °C | | |
| -40°C < Tamb < 40°C | 200°C (*)(**) | 100 °C | | |

(*) provided that the sensor tip at the sliding connection is the only part in contact with the media

(**) Maximum allowed media/process temperature.

The following warning must be present on the marking plate:
"DO NOT OPEN WHEN AN EXPLOSIVE DUST ATMOSPHERE IS PRESENT"

(b) Conditions for Use (Routine Tests):

See original certificate

Essential Health and Safety Requirements

See original certificate

DRAWINGS

| Document No. | Sheets | Document Title | Issue | Date (yyyy/mm/dd) |
|-----------------|--------|---|-------|----------------------|
| 2008970 | 1 | Etiket Level Switch LLFS 2xx Ex Dust A3 | B1 | 2010-07-27 |

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Testing & Certification Limited
Deeside Lane, Chester, CH1 6DD
Tel: + 44 (0)1244 882590 Fax: +44 (0)1244 882599

http://www.intertek.com

Registered No 3272281 Registered Office: 25 Savile Row London W1X 1AA

This Certificate is the property of Intertek Testing and Certification Ltd and is subject to Intertek Testing and Certification Conditions for Granting Certification.