

ZONE 1/22



IS RSM1.1

The wireless remote speaker mic allows professional use of push-to-talk via Bluetooth. In addition, the IS-RSM1.1 can also be used as a speaker-phone. The IS-RSM1.1 is sensible complemented with a SOS button.

› Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. › i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. › © 2018 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1013MD02REV00_EN

TECHNICAL FEATURES



ATEX approval:
EX-zone
Ⓢ II 2G Ex ib IIC T4 Gb
Ⓢ II 3D Ex ic IIIB T135°C
Dc IP54



IECEx approval:
EX-zone 1/22
Ex ib IIC T4 Gb
Ex ic IIIB T135°C Dc IP54



size: 87 x 56 x 25 mm,
weight: 126 g



950 mAh battery



amplified speaker



intercom, volume
control and channel
selection



charging with micro
USB



push-to-talk



red SOS button



operation range from
-20 °C to 60 °C

CONTENTS

remote speaker microphone, USB cable i.safe PROTECTOR, charger,
quick start manual and safety instructions