

# MX-PROTECT

## LINEAR

- MX-Protect combines the best of extrusion and injection luminaires offering high endurance and fully adaptability.
- Robust for a wide range of temperatures, up to 55°C.
- Quick and safe connection with up to 8 poles ready for through wiring, phase connection, emergency and so on.
- Innovative lever locking system, for a quick and safe mounting and prepared for vandal-proof environments.

### MOUNTING POSSIBILITIES




### TECHNICAL DATA

Rated voltage range	220V-240V
Rated frequency	0-50Hz/60Hz
Protection rating	IP66/69K
Impact resistance	IK10
Fire protection	Flammability (UL94): V2 / Glow wire test(EN 60695-2-11): 850°C
THD	< 10%
Ambient temperature	-40°C ~ +55°C
Color Rendering Index (CRI)	> 80
Type of control gear	Electronic transformer, switchable
Connection method	3-8 poles WAGO quick connector
Lifetime	L80 100,000 hours at 35°C
Guarantee	5 years

Article	Name	Luminous flux	Effect	Color temp.	Luminaire
MX40PT	MX-Protect 4000lm	4000 lm	27 W	4000 K	Linear
MX60PT	MX-Protect 6000lm	6000 lm	40 W	4000 K	Linear

### DIMENSIONS / MOUNTING DISTANCE




Art. nr.	X	Xm	Y	Z
MX40PT	1372	800	120	100
MX40PT (Through wiring)	1498	800	120	100
MX60PT	1664	1100	120	100
MX60PT (Through wiring)	1790	1100	120	100


Dimensions in mm

### PHOTOMETRICAL CHARACTERISTICS

#### DIFFUSE



#### TB



MX-Protect