

# PS12 Desktop Microphone

Desktop microphone with dynamic  
microphone and one button

## Article Number

6401-049-000-40



## Characteristics

- Rugged metal housing
- Dynamic unidirectional high-noise cancelling gooseneck microphone
- Extremely durable double switch contact

## Scope of delivery

- Desktop microphone
- Strain relief

## Options

- Customized plugs and cables
- Special button colours and symbols
- Microphone preamplifier
- Electret microphone mounted on 8 mm gooseneck
- Up to three buttons and LEDs
- Black housing

## Application range

- Radio and PA systems in fixed indoor applications

## Accessories

- WS16 windscreen (Art.-No.: 1010-042-003-64)

## Specifications

### General

Microphone head	Brass, silver
Gooseneck	Metal, silver
Housing	Metal, silver
Dimensions	Microphone head: Length 80 mm, Ø 24 mm Gooseneck: Length 200 mm, Ø 11 mm Housing: Height 32 mm, width 105 mm, depth 160 mm
Weight	650 g (22.9 oz)
Connection	Cable and plug not included
Operating and display elements	1 button, black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)

### Microphone

Frequency range	150 Hz to 12 kHz at -10 dB
Directivity	Cardioid (at 1 kHz; 180° -20 dB)
Sensitivity	1 mV/Pa (-60 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz